

PRODUCT SPEC SHEET

360 Degree Type-D Solar Powered Airport Barricade Light



| Product Type: | Airport Safety Light |
|--|---|
| Part Number: | 36oSC (Screw/Threaded Base) |
| Dual Function Mode: | Flashing &/or Steady Burn Modes All-in-One |
| Flash Rate: | +/- 65 Flashes per Minute |
| Power/Energy: | 0.4 Watt Solar Panel2.4 Volt NiMH 2,200 mAh Rechargeable Battery Included/Installed |
| Illumination/Brightness: | Multiple High-Intensity Super Bright LEDs; 9 Candelas Each |
| Operational Requirements: | Ready to Operate Right Out of the Box; All Parts Included; Maintenance Free |
| Length of Operation: | 3 to 5+ Years |
| | |
| Full Solar Charge: | Operates 168+ Hours |
| Full Solar Charge: Charging Requirements: | Operates 168+ Hours Re-Charges During Day; No Direct Sunlight Required to Charge |
| | • |
| Charging Requirements: | Re-Charges During Day; No Direct Sunlight Required to Charge |
| Charging Requirements: On/Off Switch: | Re-Charges During Day; No Direct Sunlight Required to Charge Light Automatically Turns On at Dusk & Off at Dawn |
| Charging Requirements: On/Off Switch: Lens Cover Material: | Re-Charges During Day; No Direct Sunlight Required to Charge Light Automatically Turns On at Dusk & Off at Dawn Polycarbonate |
| Charging Requirements: On/Off Switch: Lens Cover Material: Base Configuration: | Re-Charges During Day; No Direct Sunlight Required to Charge Light Automatically Turns On at Dusk & Off at Dawn Polycarbonate Standard Screw/Threaded Style Base |

Light Meets or Exceeds FAA Performance Specifications; Advisory Circular No. 150/5370-2G Compliant

